

SAFETY DATA SHEETS

This SDS packet was issued with item:

078553574

N/A

MATERIAL SAFETY DATA SHEET

Section 1: Chemical Product and Company Identification		
Product Name:	Seracult® Developer	Seracult® Plus Developer
Reorder No.	379015	377015
Also component of reorder no.:	371001, 371002, 372003, 372004, 372005, 372007, 379010	374001, 374002, 375003, 375004, 375005, 375007, 377010
Manufactured by:	Propper Manufacturing 36-04 Skillman Avenue Long Island City, NY 11101 (718) 392-6650	

Section 2: Composition and Information on Ingredients				
Hazardous Ingredients*	Approximate Concentration in Product		CAS Number	Hazardous Criteria Met:
	Seracult® Developer	Seracult® Plus Developer		
Ethanol, SDA 40 (denatured alcohol)	75 %	84 %	64-17-5	OSHA 29 CFR 1910.1200
Hydrogen Peroxide (stabilized, 35%)	5 %	4 %	7722-84-1	OSHA 29 CFR 1910.1200

*Other components are proprietary and do not pose a cause for concern

Section 3: Hazards Identification	
Emergency Overview:	Seracult developer is a clear, colorless liquid. It has an odor similar to alcohol and can irritate the eyes, skin, and respiratory tract. Both liquid and vapor of solution are flammable.
Potential Health Effects:	May cause eye, skin and respiratory tract irritation. Inhalation of ethanol may cause headaches, dizziness, drowsiness, and lassitude, loss of appetite, nausea, and vomiting. Inhalation of hydrogen peroxide may cause irritation or chemical burns to mucous membranes and the gastrointestinal tract. Serious health consequences may result from ingestion.

Section 4: First Aid Measures	
Eye Contact	Flush eyes immediately with low pressure cold water for 15 minutes or more with eyes open. Obtain medical attention.
Skin Contact	Flush contact area with cold water. Wash affected area with soap and water, rinse thoroughly. Skin that has been bleached white will return to normal color within a few hours. If irritation persists or pain ensues, seek medical attention.
Inhalation	Move victim into fresh air. If there is difficulty breathing or victim loses consciousness seek medical attention.
Ingestion	If fully conscious, and not convulsing, victim should drink 1-2 glasses of water to dilute the solution. Contact a physician or poison control center immediately. Do not induce vomiting unless instructed to do so by a certified medical authority.
Section 5: Fire Fighting Measures	
Classification	Flammable Liquid . The liquid developer will ignite in direct flame.
Flash Point	The developer was not tested. It should be considered similar to ethanol SDA 40, 190 proof: 16.1 °C (60.98 °F) Tag closed cup; 21.1 °C (69.98 °F) Tag open cup.
Flammable Limits	The developer was not tested. It should be considered similar to ethanol: 3.3% by volume (lower limit); 19% by volume (upper limit).
Extinguishing Media	Use water, carbon dioxide, dry chemicals or universal-type foams applied per manufacturer's recommendation.
Special Fire Fighting Procedures	Wear protective clothing. Use self-contained breathing apparatus (NIOSH Certified). Do not use oxidizable sorbents.
Special Fire and Explosion Hazards	Oxygen evolution from the composition of hydrogen peroxide will support combustion and may serve to intensify fire. Excessive heat may cause container pressurization, enhancing risk of explosion and fire.
Section 6: Accidental Release Measures	
Spill, Leak, and Disposal Procedures	Dilute leaks and spills with large amounts of cold water. Discharge diluted waste in accordance with local, state, and federal environmental regulations.
Section 7: Handling and Storage	
Handling Procedures	Use in well ventilated areas away from excessive heat e.g., locations in close proximity to radiators, steam, or hot water pipes, open flames, sparking equipment and all other ignition sources. Avoid contact with skin or eyes. Replace bottle closure when developer is not being used. This will diminish alcohol vapors and reduce the risk of developer contamination.

Storage Conditions	Avoid unnecessary exposure to sources of ultra violet light, e.g., direct sunlight, UV lamps and UV-emitting room lights. Store between 15° - 30°C (59° - 86°F). Do not refrigerate or freeze.
Section 8: Exposure Control/Personal Protection	
Exposure Limits	US OSHA-PEL: Hydrogen Peroxide 1 ppm TWA (1.4 mg/m ³ TWA) Ethanol 1,000 ppm (1,900 mg/m ³) ACGIH-TLV : Hydrogen Peroxide 1 ppm TWA Ethanol 1,000 ppm (1,880 mg/m ³)
Engineering Controls	Use in ventilated area.
Respiratory Protection	In well ventilated area under normal use, this product should not require respiratory protection.
Eye Protection	Safety glasses or chemical goggles should be worn to prevent eye contact.
Skin Protection	Gloves should be worn to prevent skin contact.
Section 9: Physical and Chemical Properties	
Physical State	Liquid
Appearance	Clear, colorless, water-like
Odor	Characteristic alcohol scent
Odor Threshold	Not applicable
pH	Not available
Boiling Point	81 ° C (177.8 ° F)
Freezing Point	< -20 ° C (-4 ° F)
Melting Point	Not available
Specific Gravity	0.86 at 20 ° C
Vapor Pressure	Similar to ethanol SDA 40 (~ 21 mm Hg)
Evaporation Rate	Similar to ethanol SDA 40 (~ 1.6õ butyl acetate = 1)
% Volatiles	~ 100 (by volume)
Solubility in Water	Completely miscible
Section 10: Stability and Reactivity	
Stability	This product is stable under standard conditions of temperature and pressure. Please adhere to recommended storage conditions for best results and greatest stability.
Incompatibility	Ethanol: Concentrated nitric and sulfuric acids, strong oxidizing agents.

	Hydrogen Peroxide: Rust, dirt, dust and inert particulate solids in general. Solutions with pH greater than 4. Iron, copper and a host of heavy metals, their salts and alloys. Some organic materials, reducing agents and strong oxidizing agents. Ultra violet light may induce photo decomposition.
Hazardous Polymerization	This will not occur with the developer or any of its components.
Hazardous Combustion and Decomposition Products	Ethanol: Incomplete combustion may produce carbon monoxide and/or carbon dioxide. Hydrogen Peroxide: Oxygen may be evolved resulting in a fire intensification hazard.

Section 11: Toxicological Information

Effects of Acute Exposure	<p>Primary routes of exposure are through the eyes and skin.</p> <p>Eye: The developer was not tested. Ethanol is a known eye irritant. Hydrogen peroxide is a severe (corrosive) eye irritant.</p> <p>Skin: Ethanol can cause skin irritation and prolonged contact will deplete skin of natural oils. Hydrogen peroxide may produce a mild skin burning sensation and/or bleaching or whitening of the skin. Irritation may follow prolonged contact.</p> <p>Skin Absorption: Hydrogen peroxide . LD50 > 2000 mg/kg (rabbit): FMC ref. I83-745, 1983.</p> <p>Inhalation: Ethanol may cause headaches, dizziness, drowsiness, lassitude, loss of appetite, inability to concentrate, decrease motor response, euphoria, nausea, and vomiting. Hydrogen peroxide may cause irritation or chemical burns to mucous membranes and the gastrointestinal tract. Further injury may result from a distention of the esophagus and/or stomach caused by sudden gas evolution after hydrogen peroxide decomposition. LD50 = 1270 mg/kg (female rat); FMC ref. I83-745, 1985.</p> <p>Ingestion: The developer should not be ingested. If taken internally, serious health consequences may result.</p>
Chronic Effects of Overexposure	<p>Carcinogenicity: The developer was not tested. The ethanol contained in this product does not contain carcinogenic substances. Hydrogen peroxide, IARC concludes there is inadequate evidence for humans but limited evidence in experimental animals IARC 71:671 (1999). ACGIH list hydrogen peroxide as a \pmconfirmed animal carcinogen with unknown relevance to humansq(A3).</p>

Section 12: Ecological Information

Ecotoxicity	This product is toxic to fish and all other water inhabitants.
Biodegradability	Hydrogen peroxide in water environment degrades to water and oxygen.

Section 13: Disposal Considerations	
Waste Disposal	Dispose of product in accordance to local, state, and federal environmental regulations.
Section 14: Transport Information	
US DOT	ORM-D
European ADR	Class 9 Miscellaneous Dangerous Substances and Articles
International Shipping Information	Consumer Commodity ICAO UN/ID Number: ID 8000 IATA Class 9 Miscellaneous Dangerous Goods
Canadian TDG	Product Identification Number 8000 TDG classification 9 Miscellaneous Dangerous Goods
Section 15: Regulatory Information	
US Federal and State Regulations	SARA 313 None CERCLA RG ϕ , 40 CFR 302.4 None California Proposition 65 None Pennsylvania RTK Hydrogen Peroxide Florida Substance List Hydrogen Peroxide New Jersey Dept. of Health RTK List Hydrogen Peroxide Massachusetts MSL Hydrogen Peroxide
Canada	This product is exempt from WHMIS label and MSDS requirements. Product Identification Number 8000 Hydrogen Peroxide listed under ingredient disclosure list. Ethanol listed under domestic substance list (DSL)
Section 16: Other Information	
<ul style="list-style-type: none"> Seracult® and Seracult® Plus slides and tape, included in kits with the developer products discussed above are deemed non-hazardous under the guidelines provided by the OSHA Hazard Communication standard 29 CFR 1910.1200. Please contact Propper Manufacturing for any further questions or concerns. 	

Propper Manufacturing Co., Inc. believes the information contained in this document is valid and accurate to the best of our ability based on current information available. Propper Manufacturing makes no guarantees or warranty to the validity, accuracy, or currency and shall not be liable or responsible in any way for use of either this information or materials that apply. Disposal of hazardous materials may be subject to local laws and regulations, such laws should be followed when relevant.



Seracult[®] and Seracult[®] Plus SDS

CONTROLLED DOCUMENT

SAFETY DATA SHEET

Section 1: Chemical Product and Company Identification

Product Name:	Seracult[®] Developer	Seracult[®] Plus Developer
Reorder No.:	379015	377015
Also component of reorder no.:	371001, 371002, 372003, 372004, 372005, 372007, 379010	374001, 374002, 375003, 375004, 375005, 375007, 377010
Purpose/Use:	For In Vitro Diagnostic use for Fecal Occult Blood Test. See product literature for details.	
Product Description:	Clear colorless liquid mixture with an alcohol odor in a 15mL bottle.	
Manufactured by/Contact information:	Propper Manufacturing Co. Inc. 36-04 Skillman Avenue Long Island City, NY 11101 (718) 392-6650 (Regular and Emergency Number)	

Section 2: Hazards Identification

Emergency Overview

WARNING: Avoid contact with eyes and skin. If contact occurs, flush affected area with water.

CAUTION: **Flammable.** Protect from light and heat. Keep tightly capped.

Appearance: Clear, Colorless Mixture

Physical State: Liquid

Odor: Alcohol

Potential Health Effects:

May cause eye, skin and respiratory tract irritation. Inhalation of ethanol may cause headaches, dizziness, drowsiness, and lassitude, loss of appetite, nausea, and vomiting. Inhalation of hydrogen peroxide may cause irritation or chemical burns to mucous membranes and the gastrointestinal tract. Serious health consequences may result from ingestion.

Hazard Classification of Pure Ingredients

Source of Hazard-	US - OSHA	EU – 67/548/EEC*	GHS EC NO 1272/2008 *	WHMIS*
Ethyl Alcohol:	Flammable Irritant	<ul style="list-style-type: none"> • F; • Xi • R11; • S7; S16; S36/37 	Please See <u>Table 1</u> Below	B2; D2B
Hydrogen Peroxide (stabilized, 35%):	Oxidizer Corrosive	<ul style="list-style-type: none"> • O; • C; • R8; R20/22; R35 • S17; S26; S28; S36/37; S45 	Please See <u>Table 1</u> Below	C; E

*Full text can be found under sections 16

CONTROLLED DOCUMENT

Section 2: Hazards Identification (Con't)

TABLE 1:
GHS
EC NO 1272/2008*

Classification & Labeling of Pure Ingredients				
International Chemical Identification:	Hazard Class and Category Code:	Pictogram/Signal Word Code:	Hazard Statement Codes:	Precautionary Statement Codes:
Ethyl Alcohol:	Flam. Liq. 2	 Signal Word: Danger!	H225; H335; H315 + H320	P210; P233; P280; P501; P303 + P361 + P353 P337 + P313 P370 + P378 P403 + P235
Hydrogen Peroxide (stabilized, 35%):	Ox. Liq. 1 Acute Tox. Oral 4 Acute Tox. Inhal. 4 Skin Corr. 1A	 Signal word: Danger!	H271; H302; H314; H318; H332; H335	P210; P220; P221; P264; P270; P280; P283; P363; P501; P301 + P312 + P330 P301 + P330 + P331 P303 + P361 + P353 P304 + P340 + P310 P305 + P351 + P338 + P310 P306 + P360 P370 + P378 P371 + P380 + P375

*Full text can be found under sections 16

Section 3: Composition and Information on Ingredients

Hazardous Ingredients Within The Mixture:*

Chemical Name:	Approximate Concentration in Product (% by weight):		Hazardous Criteria Met:	IDENTIFIERS:	
	Seracult® Developer	Seracult® Plus Developer			
Ethanol, SDA 40 (denatured alcohol): (Ethyl Alcohol)	75 %	84 %	OSHA 29 CFR 1910.1200	CAS#: EINECS (EC-No) #: EU Index #: PUBCHEM:	64-17-5 200-578-6 603-002-00-5 702
Hydrogen Peroxide (stabilized, 35%):	5 %	4 %	OSHA 29 CFR 1910.1200	CAS#: EINECS (EC-No) #: EU Index #: PUBCHEM:	7722-84-1 231-765-0 008-003-00-9 784

*Other components are proprietary and do not pose a cause for concern

Section 4: First Aid Measures

Eye Contact:	Flush eyes immediately with cold water for 15 minutes or more with eyes open. Obtain medical attention.
Skin Contact:	Flush contact area with cold water. Wash affected area with soap and water, rinse thoroughly. Skin that has been bleached white will return to normal color within a few hours. If irritation persists or pain ensues, seek medical attention.
Inhalation:	Move victim into fresh air. If there is difficulty breathing or victim loses consciousness seek medical attention.
Ingestion:	If fully conscious, and not convulsing, victim should drink 1-2 glasses of water to dilute the solution. Contact a physician or poison control center immediately. Do not induce vomiting unless instructed to do

so by a certified medical authority.

Section 5: Fire Fighting Measures

Flammability of the Product:	Flammable Liquid – The liquid in the developer will ignite in direct flame.
Extinguishing Media:	Use water, carbon dioxide, dry chemicals or universal-type foams applied per manufacturer’s recommendation.
Special Fire Fighting Procedures :	Wear protective clothing. Use self-contained breathing apparatus (NIOSH Certified). Do not use oxidizable sorbents.
Special Fire and Explosion Hazards:	Oxygen evolution from the composition of hydrogen peroxide will support combustion and may serve to intensify fire. Excessive heat may cause container pressurization, enhancing risk of explosion and fire.

Section 6: Accidental Release Measures

Spill, Leak, and Disposal Procedures:	Use appropriate personal protective clothing. Dilute leaks and spills with large amounts of cold water. Discharge diluted waste in accordance with local, state, and federal environmental regulations.
--	---

Section 7: Handling and Storage

Handling Precautions:	Use in well ventilated areas away from heat and sources of ignition. e.g., locations in close proximity to radiators, steam, or hot water pipes, open flames, sparking equipment and all other ignition sources. Avoid contact with skin or eyes. Replace bottle closure when developer is not being used. This will prevent the loss of alcohol vapors and reduce the risk of developer contamination.
Storage Conditions:	Avoid unnecessary exposure to sources of ultra violet light, e.g., direct sunlight, UV lamps and UV-emitting room lights. Store between 15° - 30°C (59° - 86°F) in a well-ventilated area. Do not refrigerate or freeze. Keep container sealed until ready for use.

Section 8: Exposure Control and Personal Protection

Exposure Limits:	US OSHA-PEL:	Hydrogen Peroxide: 1 ppm TWA (1.4 mg/m3 TWA)
		Ethanol: 1,000 ppm (1,900 mg/m3)
	ACGIH-TLV :	Hydrogen Peroxide: 1 ppm TWA
		Ethanol: 1,000 ppm (1,880 mg/m3)
	NIOSH-IDLH:	Hydrogen Peroxide: 75 ppm IDLH; 1ppm TWA (1.4 mg/m3 TWA)
		Ethanol: 3300ppm IDLH (10% LEL); 1,000 ppm TWA; (1,900 mg/m3 TWA)
Engineering Controls:	Use in ventilated area.	
Respiratory Protection:	In well-ventilated area under normal use, this product should not require respiratory protection.	
Eye Protection:	Safety glasses or chemical goggles should be worn to prevent eye contact.	
Skin Protection:	Gloves should be worn to prevent skin contact.	

Section 9: Physical and Chemical Properties

Physical State:	Liquid
Appearance:	Clear, colorless, water-like



Seracult[®] and Seracult[®] Plus SDS

CONTROLLED DOCUMENT

Odor:	Characteristic alcohol scent
Odor Threshold:	Not applicable
Vapor Pressure:	Not available
pH:	Not available
Boiling Point:	81°C (177.8°F)
Freezing Point:	< -20°C (-4°F)
Melting Point:	Not available
Relative Density:	Not available
Flash Point:	The developer was not tested. It should be considered similar to ethanol SDA 40, 190 proof: CLOSED CUP: 16.1°C (60.98°F); OPEN CUP: 21.1°C (69.98°F).
Flammable Limits:	The developer was not tested. It should be considered similar to ethanol SDA 40, 190 proof: : LOWER LIMIT: 3.3% by volume; UPPER LIMIT: 19% by volume.
Specific Gravity:	0.86 at 20 ° C
Vapor Pressure:	Similar to ethanol SDA 40 (~ 21 mmHg)
Evaporation Rate:	Similar to ethanol SDA 40 (~ 1.6...butyl acetate = 1)
% Volatiles:	~ 100 (by volume)
Solubility in Water:	Completely miscible

Section 10: Stability and Reactivity

Chemical Stability:	This product is stable under standard conditions of temperature and pressure. Please adhere to recommended storage conditions for best results and greatest stability.
Incompatibility:	Concentrated nitric and sulfuric acids, strong oxidizing agents, alkali metals, ammonia, rust, dirt, dust and inert particulate solids in general, solutions with pH greater than 4, Iron, copper and a host of heavy metals, their salts and alloys. Some organic materials, reducing agents and strong oxidizing agents. Ultra violet light may induce photo decomposition.
Hazardous Polymerization:	Will not occur.
Hazardous Combustion and Decomposition Products:	Incomplete combustion may produce carbon monoxide (CO) and/or carbon dioxide (CO ₂). Oxygen may be evolved resulting in a fire intensification hazard.

Section 11: Toxicological Information

Effects of Acute Exposure:

Primary routes of exposure are through the eyes, ingestion, inhalation and skin contact.
Eye: May cause eye damage in case of accidental contact.
Skin: May cause skin irritation and a mild burning sensation and/or bleaching or whitening of the skin may happen. Irritation and depletion of natural oils in the skin may follow prolonged contact.
Inhalation: May cause headaches, dizziness, drowsiness, lassitude, loss of appetite, inability to concentrate, decrease motor response, euphoria, nausea, vomiting, irritation or chemical burns to mucous membranes and the gastrointestinal tract. Further injury may result from a distention of the esophagus and/or stomach caused by sudden gas evolution after hydrogen peroxide decomposition.
Ingestion: The developer should not be ingested and maybe harmful if swallowed.

	Ethyl Alcohol:	Hydrogen Peroxide:
Toxicological Data:	Dermal LD ₅₀ (Albino Rats)	N/A
	Dermal LD ₅₀ (Rabbit)	N/A
	Oral LD ₅₀ (Albino Rats)	7060 mg/kg
	Inhalation LC ₅₀ (Albino Rats)	124.7 mg/L – 4H

Chronic Effects of Overexposure:

Carcinogenicity: The developer was not tested. The ethanol content is not a carcinogenic substance. Hydrogen peroxide, IARC concludes there is inadequate evidence for humans but limited evidence in experimental animals IARC 71:671 (1999). ACGIH list hydrogen peroxide as a 'confirmed animal carcinogen with unknown relevance to humans' (A3).
Mutagenicity: None identified.
Reproductive Toxicity: None identified.

Section 12: Ecological Information

Eco-toxicity:	This product is toxic to fish and all other water inhabitants.	
	Ethyl Alcohol:	
	<i>Fresh Water Algae:</i>	No Information Available
	<i>Fresh Water Species:</i>	LC ₅₀ <i>Oncorhynchus mykiss</i> (rainbow trout): 12.0-16.0 mL/L – 96h [static]; LC ₅₀ <i>Pimephales promelas</i> (fathead minnow): > 100mg/L – 96h [static]; LC ₅₀ <i>Pimephales promelas</i> : 13400-15100 mg/L – 96h [flow-through].
	<i>Microtox:</i>	No Information Available
	<i>Water Flea:</i>	EC ₅₀ <i>Daphnia Magna</i> : 10800 mg/L – 24h; EC ₅₀ <i>Daphnia Magna</i> : 9268-14221 mg/L – 48h; EC ₅₀ <i>Daphnia Magna</i> : 2 mg/L – 48h [static].
	Hydrogen Peroxide:	
	<i>Fresh Water Algae:</i>	EC ₅₀ <i>Chlorella vulgaris</i> : 2.5 mg/L- 72h.
	<i>Fresh Water Species:</i>	LC ₅₀ <i>Oncorhynchus mykiss</i> (rainbow trout): 10.0-32.0 mL/L – 96h [static]; LC ₅₀ <i>Pimephales promelas</i> (fathead minnow): 16.4 mL/L – 96h; LC ₅₀ <i>Lepomis macrochirus</i> (Bluegill): 18-56 mg/L [static] -96h.
	<i>Microtox:</i>	No Information Available.
	<i>Water Flea:</i>	EC ₅₀ <i>Daphnia Magna</i> : 7.7 mg/L – 24h; EC ₅₀ <i>Daphnia Magna</i> : 18-32 mg/L – 48h [static].

Biodegradability: Hydrogen peroxide in water environment degrades to water and oxygen.

Section 13: Disposal Considerations

Waste Disposal: Dispose of waste and unused product in compliance with local, state, and federal environmental regulations. If unsure of waste requirements, contact a licensed professional waste disposal service to dispose of this material if questions arise.

Section 14: Transport Information

Section 14: Transport Information					
Shipping Information	US: DOT	European (Land Transport): ADR/RID	International Shipping Information		Canadian: TDG
			Maritime Transport: IMO/IMDG	Air Transport: IATA-DGR/ ICAO-TI	
UN/ID Number:	3316				
Proper Shipping Name:	Chemical Kit (contains ethanol solution)				
Hazard Class: (Subsidiary Class)	Hazard Class 9- Miscellaneous Dangerous Goods; Subsidiary Class 3- Flammable Liquid				
Packing Group:	PG II	PG II	PG II	PG II	PG II
Special Comment:	NA ERG Code: 171				

Section 15: Regulatory Information

US Federal and State Regulations:	SARA 313:	No ingredients listed.
	CERCLA RG's (40 CFR 302.4)	No ingredients listed.
	TSCA	No ingredients listed.
	California Proposition 65:	No ingredients listed.
	Massachusetts MSL:	Hydrogen Peroxide is listed. Ethyl Alcohol is listed.
	New Jersey Dept. of Health RTK List: (RTK Substance number)	Hydrogen Peroxide is listed (1015). Ethyl Alcohol is listed (0844).
	Pennsylvania RTK:	Hydrogen Peroxide is listed. Ethyl Alcohol is listed.
	Rhode Island Hazardous Substance List:	Ethyl Alcohol is listed.
Canada:	This product is exempt from WHMIS label and SDS requirements. Product Identification Number: 3316 Disclosure list ingredient: Hydrogen Peroxide & Ethyl Alcohol.	
EU Regulations:	Water Hazard Class (Germany): WGK 1, low water endangering.	

Section 16: Other Information

- Seracult® and Seracult® Plus slides and tape, included in kits with the developer products discussed above are deemed non-hazardous under the guidelines provided by the OSHA Hazard Communication standard 29 CFR 1910.1200.

Full text of EU – 67/548/EEC Risk and Safety Phrases under sections 2

Risk Phrase:

- R8- Contact with combustible material may cause fire.
- R11- Highly flammable liquid category 2.
- R34- Causes burns.
- R20/22 - Harmful by inhalation and if swallowed

Safety Phrase:

- S7- Keep container tightly closed.
- S16- Keep away from sources of

Full text of GHS Hazard and Precautionary Statements under sections 2

Hazard statement(s)

- H225: Highly flammable liquid and vapor.
- H271: May cause fire or explosion; strong oxidizer.
- H302: Harmful if swallowed.
- H314: Causes severe skin burns and eye damage.
- H318: Causes serious eye damage.
- H332: Harmful if inhaled
- H335: May cause respiratory irritation.
- H315 + H320: Causes skin and eye irritation

Precautionary statement(s)

- P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P220: Keep/Store away from clothing/ combustible materials.

- ignition – No smoking.
- S17- Keep away from combustible material.
- S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S28- After contact with skin, wash immediately with plenty of water.
- S45- In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).
- S36/37- Wear suitable protective clothing and gloves.

Additional Phrases:

C- Corrosive	
F-Highly Flammable	
O- Oxidizing	
Xi – Irritant	

- P221: Take any precaution to avoid mixing with combustibles.
- P233: Keep container tightly closed.
- P264: Wash skin thoroughly after handling.
- P270: Do not eat, drink or smoke when using this product.
- P273: Avoid release to the environment.
- P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P283: Wear fire/ flame resistant/ retardant clothing.
- P363: Wash contaminated clothing before reuse.
- P501: Dispose of contents/ container to an approved waste disposal plant.
- P301 + P312 + P330: IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
- P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303 + P361 + P353: IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304 + P340 + P310: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
- P305 + P351 + P338 + P310: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
- P306 + P360: IF ON CLOTHING: rinse immediately contaminated clothing and skin with plenty of water before removing clothes.
- P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
- P371 + P380 + P375: In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
- P337 + P313: If eye irritation persists: Get medical attention.
- P403 + P235: Store in a well-ventilated place. Keep cool.

- Full text of WHMIS under section 2

B2- Flammable liquid: Flashpoint of < 37.8°C (100°F)	
C- Oxidizing material	
D2B – Toxic material at >1%; Skin/Eye Irritation	
E- Corrosive material at >1%	

Acronyms and Abbreviations:

GHS- Globally Harmonized System
 WHMIS- Workplace Hazardous Materials Information System
 ACGIH- American Conference of Governmental Industrial Hygienists
 TLV- Threshold Limit Value
 NIOSH- National Institute for Occupational Safety and Health
 IDLH- Immediately Dangerous to Life or Health
 OSHA- Occupational Safety and Health Act
 PEL- Permissible Exposure Limit
 TWA- Time-Weighted Average
 LD₅₀ –Lethal Dose, 50%
 LC₅₀ -Lethal Concentration, 50%
 EC₅₀ -Effective Concentration, 50%
 SARA- Superfund Amendments and Reauthorization Act
 CERCLA- Comprehensive Response Compensation, and Liability Act
 TSCA- Toxic Substance Control Act
 RTK- Right to Know

- Please contact Propper Manufacturing for any further questions or concerns.

This SDS was last prepared on **18-Nov-2015**



Seracult[®] and Seracult[®] Plus SDS

CONTROLLED DOCUMENT

Propper Manufacturing Co., Inc. believes the information contained in this document is valid and accurate to the best of our ability based on current information available. Propper Manufacturing makes no guarantees or warranty to the validity, accuracy, or currency and shall not be liable or responsible in any way for use of either this information or materials that apply. Disposal of hazardous materials may be subject to local laws and regulations, such laws should be followed when relevant.